

VHF DIGITAL SIGNAL BOOSTERS

137 - 174 MHz • 1.6MHz min Banguard

DH124

Product Features

- Channel Selective, software programmable
- Fully digital signal boosters, FPGA based
- Auto diagnostic
- Uplink squelch, per channel and per time slot
- User adjustable gain control, UL and DL independent, per channel
- Automatic Gain Control, per channel and per time slot
- Weatherproof enclosure, IP67/NEMA4X
- NFPA compliant
- Built in spectrum analyzer



Applications

- Indoor coverage: tunnels and mobile fast-deploy communication units
- Outdoor coverage: oil rigs, stadiums, dense urban areas, rural areas, cliffs

Specification

Value

Specification	Value
Type	Digital Signal Boosters (without Antenna Feedback Cancellation)
Frequency range	137 - 174 MHz
Downlink BW	3.50MHz
Uplink BW	3.50MHz
UL to DL bandguard	1.60MHz min
Passband BW. min	Channel Selective (180KHz, 90KHz, 45KHz, 30KHz, 20KHz, and 15KHz BW)
Number of Passband	Channel Selective (180KHz, 90KHz, 45KHz, 30KHz, 20KHz, and 15KHz BW), 1 to 32
Gain, maximum	70 dB
Passband ripple	+/- 2.0 dB
Gain, manual control	28dB range, digitally controlled in 1dB steps
Antenna isolation	Max Gain + 15 dB
Composite output power, DL	+24 dBm composite
Composite output power, UL	+24 dBm composite
IM and spurious generation	< -13 dBm
Noise figure	9.0 dB max at maximum gain
Impedance	50 Ω
Group delay	Channel Selective 180KHz, 12μS Channel Selective 90KHz, 14μS Channel Selective 45KHz, 23μS Channel Selective 30KHz, 32μS Channel Selective 20KHz, 45μS Channel Selective 15KHz, 55μS
Maximum input power, no damage	0 dBm (UL) 0 dBm (DL)

DOC BD299.02 - 21022018 - DM
 Fiplex is a registered trademark of Fiplex Communications, Inc.
 Fiplex Communications, Inc. reserves the right to change specifications without prior notice.

VHF DIGITAL SIGNAL BOOSTERS

137 - 174 MHz • 1.6MHz min Banguard

DH124

Specification	Value
Connectors	N(f) as standard
VSWR at operating frequencies	1.5:1 max
Uplink squelch function	Yes, user selectable, to avoid UL noise when no carriers present, by time slot and by channel (Channel Selective model only)
Self diagnostic platform	Microprocessor based
Alarms	Yes, amplifiers status, power amplifiers status, power supply failure, battery backup failure, temperature, AGC, RF overload, poor antenna isolation.
Local management and supervising	Local access via USB and Ethernet (web browser)
Remote management and supervising	Remote access via Ethernet. Wireless modem, SNMP as optional.
RoHS compliance	Yes
AC Supply	110/220 VAC, 50/60 Hz
Power Consumption	170 W
DC Supply	+24VDC & -48VDC
Housing	IP67 / NEMA4X
Temperature range	-13° to 131° F • -25° to +55° C
Cooling	Natural convection
Dimension	30 x 24 x 15 inches • 762 x 610 x 305 mm
Mounting	Wall mounting
MTBF	<50.000 hours

MODEL	NFPA	POWER in dBm	110-220VAC	24VDC & -48VDC
DH124-313	950	24	X	
DH124-314	950	24		X
DH124-319	950	24	X	
DH124-320	950	24		X