

PUBLIC SAFETY 800 MHz DIGITAL SIGNAL BOOSTERS

PS800 MHz • Class A

DHS37

Product Features

- Channel Selective, software programmable
- Fully digital signal boosters, FPGA based
- 32 channel independent UL and DL
- Auto diagnostic
- Uplink and downlink squelch, per channel and per time slot
- User adjustable gain control, UL and DL independent, per channel
- Automatic Gain Control, per channel and per time slot
- Weatherproof enclosure, IP67/NEMA4X
- NFPA compliant
- Built-in input and output spectrum analyzer



DHS30 Digital Signal Boosters

Applications

- For P25, TETRA, DMR, NXDN and Conventional systems
- Indoor coverage: tunnels and mobile fast-deploy communication units
- Outdoor coverage: oil rigs, stadiums, dense urban areas, rural areas, cliffs



Specification

Value

Specification	Value
Type	Digital Signal Boosters
Frequency range	806-824 / 851-869 MHz
Passband BW. min	Channel Selective (90KHz, 45KHz, 30KHz, 20KHz, and 15KHz BW)
Number of Passband	Channel Selective (90KHz, 45KHz, 30KHz, 20KHz, and 15KHz BW), 1 to 32
Gain, maximum	80dB
Passband ripple	+/- 2.0 dB
Gain, manual control	28dB range, digitally controlled in 1dB steps
Antenna isolation	Max Gain + 15dB
Composite output power, DL	+37dBm
Composite output power, UL	+24dBm
IMD	< -13dBm
Noise figure	9.0dB max at maximum gain
Group delay	Channel Selective 90KHz, 14µS Channel Selective 45KHz, 23µS Channel Selective 30KHz, 32µS Channel Selective 20KHz, 45µS Channel Selective 15KHz, 55µS
Maximum input power, no damage	0dBm (UL) -35dBm (DL)
Connectors	N(f) as standard
RF Input/Output impedance	50Ω
Uplink squelch function	Yes, user selectable, to avoid UL noise when no carriers present, by time slot and by channel (Channel Selective model only)
Self diagnostic platform	Microprocessor based

DOC BD321.01 - 09082018 - FS
 Fiplex is a registered trademark of Fiplex Communications, Inc.
 Fiplex Communications, Inc. reserves the right to change specifications without prior notice.

PUBLIC SAFETY 800 MHz DIGITAL SIGNAL BOOSTERS

PS800 MHz • Class A

DHS37

Specifications	Value
Alarms	Yes, amplifiers status, power amplifiers status, power supply failure, temperature, AGC, RF overload.
Local management and supervising	Local access via USB and Ethernet (web browser)
Remote management and supervising	Remote access via Ethernet. Wireless MODEM (SNMP) as optional (RC-G)
RoHS compliance	Yes
AC Supply	110VAC, 50/60 Hz.
Power Consumption	220W
DC Supply	+24VDC & -48VDC
Housing	IP67 / NEMA4X
Temperature range	-13° to 131° F • -25° to +55° C
Cooling	Natural convection
Dimensions	20.2 x 18.2 x 9 inches • 514 x 462 x 230 mm
Weight	55 lbs • 25 Kg
Mounting	Wall mounting
MTBF	>50.000 hours

MODELO	NFPA	RC-G	110-220VAC	+24VDC / -48VDC
DHS37-600	X		X	
DHS37-601	X			X
DHS37-602	X	X	X	
DHS37-603	X	X		X

DOC BD321.01 - 09082018 - FS
 Fiplex is a registered trademark of Fiplex Communications, Inc.
 Fiplex Communications, Inc. reserves the right to change specifications without prior notice.

WARNING: This is NOT a CONSUMER device. It is designed for installation by FCC LICENSEES and QUALIFIED INSTALLERS. You MUST have an FCC LICENCE or express consent of an FCC Licensee to operate this device. Unauthorized use may result in significant forfeiture penalties, including penalties in excess of \$100,000 for each continuing violation.