

VHF DIGITAL SIGNAL BOOSTERS

155 - 174 MHz • 1 or 2 or 3 channels

DH124-323 **DH124-326**
DH124-324 **DH124-327**
DH124-325 **DH124-328**

Product Features

- Channel Selective, software programmable
- Fully digital signal boosters, FPGA based
- Auto diagnostic
- Uplink squelch, per channel and per time slot
- User adjustable gain control, UL and DL independent, per channel
- Automatic Gain Control, per channel and per time slot
- Weatherproof enclosure, IP67/NEMA4X
- NFPA compliant
- Built in spectrum analyzer



Applications

- Indoor coverage: tunnels and mobile fast-deploy communication units
- Outdoor coverage: oil rigs, stadiums, dense urban areas, rural areas, cliffs



Specification

Value

Type	Digital Signal Boosters (without Antenna Feedback Cancellation)
Frequency range	155 - 174 MHz
Downlink BW	25KHz
Uplink BW	25KHz
UL to DL bandguard	100KHz
Passband BW. min	25KHz
Number of Passband	1 or 2 or 3
Gain, maximum	80 dB
Passband ripple	+/- 2.0 dB
Gain, manual control	28dB range, digitally controlled in 1dB steps
Antenna isolation	Max Gain + 15 dB
Composite output power, DL	1 channel: +13 dBm; 2 or 3 channels: +10dBm
Composite output power, UL	1 channel: +13 dBm; 2 or 3 channels: +10dBm
IM and spurious generation	< -13 dBm
Noise figure	9.0 dB max at maximum gain
RF Input/Output impedance	50 Ω
Connectors	N(f) as standard
Uplink squelch function	Yes, user selectable, to avoid UL noise when no carriers present, by time slot and by channel (Channel Selective model only)
Self diagnostic platform	Microprocessor based
Alarms	Yes, amplifiers status, power amplifiers status, power supply failure, battery backup failure, temperature, AGC, RF overload, poor antenna isolation.
Local management and supervising	Local access via USB and Ethernet (web browser)
Remote management and supervising	Remote access via Ethernet. Wireless modem, SNMP as optional.
RoHS compliance	Yes

DOC BD344.00 - 06052019 - DM
 Fiplex is a registered trademark of Fiplex Communications, Inc.
 Fiplex Communications, Inc. reserves the right to change specifications without prior notice.

VHF DIGITAL SIGNAL BOOSTERS

155 - 174 MHz • 1 or 2 or 3 channels

DH124-323 **DH124-326**
DH124-324 **DH124-327**
DH124-325 **DH124-328**

Specification	Value
Power Supply	See table
Power Consumption	1 channel: 200W 2 channels: 230W 3 channels: 260W
Housing	IP67 / NEMA4X
Temperature range	-13° to 131° F • -25° to +55° C
Cooling	Natural convection
Dimension	30 X 24 X 12 inches • 762 X 610 X 305 mm
Mounting	Wall mounting
MTBF	<50.000 hours

Product Code	Class	Configuration	Output PWR Channel	PWR Supply Option
DH124-323	A - 1 channel UL 1 channel DL	01	+13dBm	AC
DH124-324	A - 1 channel UL 1 channel DL	01	+13dBm	DC
DH124-325	A - 2 channel UL 2 channel DL	01	+10dBm	AC
DH124-326	A - 2 channel UL 2 channel DL	01	+10dBm	DC
DH124-327	A - 3 channel UL 3 channel DL	01	+10dBm	AC
DH124-328	A - 3 channel UL 3 channel DL	01	+10dBm	DC

DOC BD344.00 - 06052019 - DM
 Fiplex is a registered trademark of Fiplex Communications, Inc.
 Fiplex Communications, Inc. reserves the right to change specifications without prior notice.