

UHF DIGITAL SIGNAL BOOSTERS

453 - 454 / 458 - 459 & 460 - 462 / 465 - 467 MHz

DH430-342

DH430-343

Product Features

- Channel Selective, software programmable
- Fully digital signal boosters, FPGA based
- Auto diagnostic
- Uplink squelch, per channel and per time slot
- User adjustable gain control, UL and DL independent, per channel
- Automatic Gain Control, per channel and per time slot
- Weatherproof enclosure, IP67/NEMA4X
- NFPA compliant
- Built in spectrum analyzer

Applications

- For P25, TETRA, DMR, NXDN and Conventional systems
- Indoor coverage: tunnels and mobile fast-deploy communication units
- Outdoor coverage: oil rigs, stadiums, dense urban areas, rural areas, cliffs



Specification

Value

Type	Digital Signal Boosters
Frequency range	453 - 454 / 458 - 459 & 460 - 462 / 465 - 467 MHz
Passband BW. min	Channel Selective (90KHz, 45KHz, 30KHz, 20KHz, and 15KHz BW)
Number of Passband	Channel Selective (90KHz, 45KHz, 30KHz, 20KHz, and 15KHz BW), 1 to 32
Gain, maximum	70dB
Passband ripple	+/- 3dB
Gain, manual control	28dB range, digitally controlled in 1dB steps
Composite output power, DL	+30dBm
Composite output power, UL	+24dBm
IMD and Spurs	<-13dBm
Noise figure	9dB at maximum gain
Group delay	Channel Selective 90KHz, 14µS Channel Selective 45KHz, 23µS Channel Selective 30KHz, 32µS Channel Selective 20KHz, 45µS Channel Selective 15KHz, 55µS
Maximum input power, no damage	0dBm (UL) -35dBm (DL)
Connectors	N(f) as standard
RF Input/Output impedance	50Ω
Uplink squelch function	Yes, user selectable, to avoid UL noise when no carriers present, by time slot and by channel (Channel Selective model only)

UHF DIGITAL SIGNAL BOOSTERS

453 - 454 / 458 - 459 & 460 - 462 / 465 - 467 MHz

DH430-342
DH430-343

Specifications	Value
Self diagnostic platform	Microprocessor based
Alarms	Yes, amplifiers status, power amplifiers status, power supply failure, temperature, AGC, RF overload.
Local management and supervising	Local access via USB and Ethernet (Web Browser)
Remote management and supervising	Remote access via Ethernet. Wireless MODEM (SNMP) as optional (RC-G)
RoHS compliance	Yes
Power Supply	See table
Power Consumption	170W
Housing	IP67 / NEMA4X
Temperature range	-13° to 131° F • -25° to +55° C
Cooling	Natural convection
Dimension	30 x 24 x 12 inches • 762 x 610 x 305 mm
Mounting	Wall mounting
MTBF	>50.000 hours

Product Code	Class	Configuration	Composite Output PWR	PWR Supply Option
DH430-342	A - 32 channel UL 32 channel DL	01	+30dBm	AC
DH430-343	A - 32 channel UL 32 channel DL	01	+30dBm	DC