


# BATTERY BACKUP SYSTEMS

## BTTY Series

### Product Features

- NFPA Compliant
- Up to 24 hour version
- Batteries included
- AC Input, 24 Volt DC Output
- NEMA-4 Rated BBU Enclosure
- Up to 4 Annunciators may be connected to one BBU
- Tamper Proof with Lock and Key Accessibility
- Flush Wall Mounted Annunciators



### Specification

Specification	Value
Type	Battery Backup Unit
Input	120 VAC 50/60 Hz
Size	24 x 20 x 10 in

### Specifications

Specifications	BTTY-100050
Storage capacity	100W / 12hs
Annunciator	AC Power Normal AC Power Failure Battery Capacity <30% Battery Charger Fail Donor Antenna Disconnection Donor Antenna Malfunction RF Emitter Fail System Component Fail
Max Load	270 W (contact Fiplex for battery duration at different loads)
Batteries	Included
BDA Annunciator	Built in, port for additional external annunciators
Weight (batteries included)	150lbs

### Specifications

Specifications	BTTY-100100
Storage capacity	100 W / 24 hs or 200 W / 12 hs
Annunciator	AC Power Normal AC Power Failure Battery Capacity <30% Battery Charger Fail Donor Antenna Disconnection Donor Antenna Malfunction RF Emitter Fail System Component Fail
Max Load	270 W (contact Fiplex for battery duration at different loads)
Batteries	Included
BDA Annunciator	Built in, port for additional external annunciators
Weight (batteries included)	210lbs

DOC BDT105.02 • 12152020 • FS  
 Fiplex is a registered trademark of Fiplex Communications, Inc.  
 Fiplex Communications, Inc. reserves the right to change specifications without prior notice.