

BATTERY BACKUP SYSTEMS

BTTY Series

Product Features

- NFPA Compliant
- Up to 24 hour version
- Batteries included
- AC Input, 24 Volt DC Output
- NEMA-4 Rated BBU Enclosure
- Up to 4 Annunciators may be connected to one BBU
- Tamper Proof with Lock and Key Accessibility
- Flush Wall Mounted Annunciators
- IFC & NFPA compliance; UL2524 2nd Edition Listing with SGS, Nationally Recognized Testing Laboratory (NRTL) approved by OSHA for UL2524
- Buy American Compliant: Meets the definition of Domestic Construction Material under the Buy American Act



Specification

Specification	Value
Type	Battery Backup Unit
Input	120 VAC 50/60 Hz
Size	24 x 20 x 10 in
Max operating temperature	55° C - 131 ° F

Specifications

Specifications	BTTY-100050
Storage capacity	100W / 12hs
Annunciator	AC Power Normal AC Power Failure Battery Capacity <30% Battery Charger Fail Donor Antenna Disconnection Donor Antenna Malfunction RF Emitter Fail System Component Fail
Max Load	270 W (contact Fiplex for battery duration at different loads)
Batteries	Included
BDA Annunciator	Built in, port for additional external annunciators
Weight (batteries included)	150lbs

Specifications

Specifications	BTTY-100100
Storage capacity	100 W / 24 hs or 200 W / 12 hs
Annunciator	AC Power Normal AC Power Failure Battery Capacity <30% Battery Charger Fail Donor Antenna Disconnection Donor Antenna Malfunction RF Emitter Fail System Component Fail
Max Load	270 W (contact Fiplex for battery duration at different loads)
Batteries	Included
BDA Annunciator	Built in, port for additional external annunciators
Weight (batteries included)	210lbs

DOC BD105.03 - 08242021 - DMC
 Fiplex is a registered trademark of Fiplex Communications, Inc.
 Fiplex Communications, Inc. reserves the right to change specifications without prior notice.