

PS 800 DIGITAL SIGNAL BOOSTERS

DHS37-600 DHS37-601

Product Features


- Channel Selective, software programmable or adjustable bandwidths
- Fully digital signal boosters, FPGA based
- Auto diagnostic
- Uplink and downlink squelch, per channel and per time slot
- User adjustable gain control, UL and DL independent, per channel
- Automatic Gain Control per channel, per time slot
- Weatherproof enclosure, IP67/NEMA4X
- Built-in input and output spectrum analyzer
- NFPA compliant

Applications

- For P25, PH I & PH II, TETRA, DMR, NXDN and Conventional systems
- Indoor coverage: tunnels and mobile fast-deploy communication units
- Outdoor coverage: oil rigs, stadiums, dense urban areas, rural areas, cliffs

Specification Value

Type	Digital Signal Boosters
Frequency range	806-824 / 851-869 MHz
Passband BW. min	Channel Selective (90KHz, 45KHz, 30KHz, 20KHz, and 15KHz BW) or 100KHz to full band (depends of configuration)
Number of Passband	Channel Selective (90KHz, 45KHz, 30KHz, 20KHz, and 15KHz BW), 1 to 32. or 8 UL & 8 DL (depends of configuration)
Gain, maximum	80 dB
Passband ripple	+/- 3.0 dB
Gain, manual control	28dB range, digitally controlled in 1dB steps, per link, per band
Antenna isolation	Max Gain + 15dB
Composite output power, DL	+37dBm
Composite output power, UL	+24dBm
IMD	< -13dBm
Noise figure	9.0dB max
Group delay	Channel Selective 90KHz, 14µs Channel Selective 45KHz, 23µs Channel Selective 30KHz, 32µs Channel Selective 20KHz, 45µs Channel Selective 15KHz, 55µs or Band Selective 12µs
Maximum input power, no damage	0dBm (UL) -35dBm (DL)



DOC BD363.00 - 05202019 - DM
 Fiplex is a registered trademark of Fiplex Communications, Inc.
 Fiplex Communications, Inc. reserves the right to change specifications without prior notice.

PS 800

DIGITAL SIGNAL BOOSTERS

DHS37-600

DHS37-601

Specifications	Value
Connectors	N(f) as standard
RF Input/Output impedance	50Ω
Uplink squelch function	Yes, user selectable, to avoid UL noise when no carriers present, per time slot and by channel
Self diagnostic platform	Microprocessor based
Alarms	Yes, amplifiers status, power amplifiers status, power supply failure, temperature, AGC, RF overload.
Local management and supervising	Local access via USB and Ethernet (web browser)
Remote management and supervising	Remote access via Ethernet. Wireless MODEM (SNMP) as optional (RC-G)
RoHS compliance	Yes
Power Supply	AC 110 VAC, 50/60 Hz or DC +24VDC & -48VDC (depends of configuration)
Power consumption	220W
Housing	IP67 / NEMA4X
Temperature range	-13° to 131° F • -25° to +55° C
Cooling	Natural convection
Dimension	18.2 x 20.2 x 9 inches • 462 x 514 x 230 mm
Weight	59.5 lbs • 27kg
Mounting	Wall or pole mounting
MTBF	250.000 hours

Product Code	Class	Config.	Composite Output Power	Power Supply Option
DHS37-600	A - 32 channels UL 32 channels DL	01	+ 37dBm per band	AC
DHS37-600	B - 8 Subbands UL 8 Subbands DL	02	+ 37dBm per band	AC
DHS37-601	A - 32 channels UL 32 channels DL	01	+ 37dBm per band	DC
DHS37-601	B - 8 Subbands UL 8 Subbands DL	02	+ 37dBm per band	DC

DOC BD363.00 - 05202019 - DM
 Fiplex is a registered trademark of Fiplex Communications, Inc.
 Fiplex Communications, Inc. reserves the right to change specifications without prior notice.

WARNING: This is NOT a CONSUMER device. It is designed for installation by FCC LICENSEES and QUALIFIED INSTALLERS. You MUST have an FCC LICENCE or express consent of an FCC Licensee to operate this device. Unauthorized use may result in significant forfeiture penalties, including penalties in excess of \$100,000 for each continuing violation.