

FLEX 2.0 - High Power Over-the-Air Public Safety Centric Fiber DAS (136-512 MHz)

HONBDA Series

Product Features

- Specifically designed for VHF and UHF, LMR and Public Safety Applications.
- No need of “Front End BDA” or “POI”, reduced infrastructure cost.
- Supports Over-the-Air (OTA) operation – Direct Donor antenna Connection to Master.
- **FLEX 2.0*** Enhanced Scalability and Flexibility – Remote Unit connection count capability up to 56 using Expansion Units.
- New improved **FLEX 2.0*** user-friendly Graphic User Interface.
- New **FLEX 2.0*** Alarming Features. All alarms of all the Remotes and BBUs of the System are available at the Master Unit.
- Enhanced **FLEX 2.0*** Redundancy Features (optional). Field expandable
- Inclusion of **FLEX 2.0*** Multiple AGC modes to allow extra Uplink Output Power Per Channel.
- Remote Units equipped with Uplink Squelch and AGC per Channel and Time-Slot (support for P25PH2) to provide truly reduced UL Noise contribution and Near-Far effect mitigation.
- Upon expansion of an existing system, no need to recommission the previously installed sections.
- Isolation Measurement and Isolation Detection in a per Remote Basis. Upon oscillation detection, only the affected area will be turned off.
- Software programmable channel selective or band selective operation, suitable for highly congested RF environments.
- Centralized operation form Master Unit. Single point of access.
- IFC 2015, 2018, 2021 Edition Standard.
- NFPA 72 2013 Edition, NFPA 1221 2016 2019 Edition Standard.
- SGS C-US Compliant.
- UL2524 2nd Edition Listing with SGS, Nationally Recognized Testing Laboratory (NRTL) approved by OSHA for UL2524.



Applications

- For P25 Ph1, P25 Ph2, DMR, TETRA, TETRAPOL, C2000, NXDN and Conventional Systems
- Tunnels, buildings, subways, airports, stadiums, building campuses, etc.

Specification

Value

Fiber-Optic	Single mode
WDM	Yes
Optical Wavelengths	1270 / 1330 nm
Operational Bands	136 - 174 MHz & 450 - 512 MHz
Number of Channel Filters	64 channels + 4 Bandwidth Adjustable per band
Available Channel Filter BW	100KHz, 75KHz, 62.5KHz, 50KHz, 37.5KHz, 25KHz & 12.5KHz
	Channel Selective 100KHz, 12.6µS Channel Selective 75KHz, 14.9µS Channel Selective 62.5KHz, 16.8µS Channel Selective 50KHz, 19.6µS Channel Selective 37.5KHz, 24.1µS Channel Selective 25KHz, 33.4µS Channel Selective 12.5KHz, 62.1µS or Band selective: 3.5 to 6.5µS. depending on BWA
Supported Fiber Loss	20dB0 max
Optical connectors	LC/UPC
Optical return loss	>45dB
RF Input/Output Impedance	50
RF connectors	N(f)
Overall gain (Master + Remote)	85dB regardless fiber length (see Note 1)
Noise Figure	<9dB

* A **FLEX 2.0** Master Unit is any PSC DAS Master Unit with firmware version equal or greater than **[SW: 5.00]**.

** A **FLEX 2.0** Remote Unit is any PSC DAS Remote Unit with firmware version equal or greater than **[SW: 3.00]**.

Master Unit Electrical and Mechanical Specifications**Value**

DL Manual Attenuator	30dB in 1dB steps
Maximum UL Output Power	+24 dBm per band (see Note 1)
UL IM and Spurious Generation	< -13dBm
UL Manual Attenuator	30dB in 1dB steps
Max Operational DL Input Power	-35dBm
Number of Optical Ports	8 (for Remote Unit and Expansion Unit connection)
Power Supply	110VAC 60Hz or +24VDC (see ordering information at the end of this document)
Power Consumption	70W
Housing	NEMA4, UL 50 Certified
Environmental	EN 300 019 4.1
Temperature range	-22° to +131° F • -30° to +55° C
Humidity	<95% non-condensing
Dimensions	Cabinet Type "C": 27,2 x 20 x 9 in (690.88 x 508.0 x 228.6mm) Cabinet Type "E": 30 x 24 x 14 in (762 x 610 x 355.6 mm)
MTBF	50.000 hours

Remote Unit Electrical and Mechanical Specifications**Value**

Composite Output Power, DL	VHF: 30 dBm, UHF: 37 dBm (see Note 1)
DL IMD and Spurious Generation	< -13 dBm
Number of Optical Ports	1 as standard, 2 optional for redundancy
UL Maximum Input Power	0dBm
UL Noise Reduction	UL squelch per channel, programmable
Manual Attenuator	20dB in 1 dB steps
Power Supply	110VAC 60Hz & +24VDC (see ordering information at the end of this document)
Power Consumption	130W
Housing	NEMA4, UL50 Certified
Environmental	EN 300 019 4.1
Temperature Range	-22° to +131° F • -30° to +55° C
Humidity	< 95% non-condensing
Dimension and Weight	(762x609.6x468.95 mm)
MTBF	50.000 hours

Control and Alarms**Value**

Alarms Report	Alarms of all the Remotes and BBUs of the System available at the Master Unit. At Master Unit via USB: Master Unit, Expansion Unit and Remote Unit Status. At Master Unit via Web browser: Master Unit, Expansion Unit and Remote Unit Status. At Master Unit via SNMP: Master Unit, Expansion Unit and Remote Unit Status. At Master Unit, alarms of Master Unit, Expansion Unit and Remote Unit Status can be reported via local Dry Contact or via serial connection to Next Gen BBU. At Remote Unit via USB: Remote Unit Status At Remote Unit, alarms of Remote Unit can be reported via local Dry Contact or via serial connection to Next Gen BBU.
Master Unit Configuration	Local: USB or Ethernet (Web browser) Remote: Via SNMP or Web browser

Normative	Value
Standards	ITU T G 652 EN60825-1
FCC	FCC, CFR 47, Part 15, Subpart B, Class A digital devices
FCC ID Master	P3TDH14-4A / P3TDH14-4B
FCC ID Remote	P3TDH14-6A / P3TDH14-6B

Note 1: Value valid for non-duplexed units. This value can change depending on the filtering insertion loss of the duplexer.

Standards and Codes

These listings and approvals apply to the modules specified in this document. In some cases, certain modules or applications may not be listed by certain approval agencies, or listing may be in process. Consult factory for latest listing status.

- FCC Certified
- IC Certified
- FC 2015, 2018, 2021 Edition Standard
- ISO 9001 PECB Certified
- NFPA 72 2019 Edition, NFPA 1225 2022 Edition Standard
- NFPA 1221, 2016, 2019 Edition Standard
- ROHS compliant
- UL2524 3rd Edition 2024 Listing with SGS, Nationally Recognized Testing Laboratory (NRTL) approved by OSHA for UL2524

Ordering Information

HONBDA-R1A-VUTNNG: Fiber DAS. OTA PUBLIC SAFETY CENTRIC DAS REMOTE DUAL BAND. VHF 136-174MHz & UHF 450-512MHz. VHF: +37dBm, UHF: +37dBm, 32filters + 2 Adj sub band per Band, 1 optical port, NFPA, AC, VHF: No Internal Duplexer, UHF: No Internal Duplexer ,UL2524 2nd Edition Listed FIPLEX BY HONEYWELL Fiber DAS

HONBDA-R1A-VUTNNH: Fiber DAS. OTA PUBLIC SAFETY CENTRIC DAS REMOTE DUAL BAND. VHF 136-174MHz & UHF 450-512MHz. VHF: +30dBm, UHF: +37dBm, 32filters + 2 Adj sub band per Band, 1 optical port, NFPA, AC, VHF: No Internal Duplexer, UHF: No Internal Duplexer ,UL2524 2nd Edition Listed FIPLEX BY HONEYWELL Fiber DAS

HONBDA-R1D-VUTNNG: Fiber DAS. OTA PUBLIC SAFETY CENTRIC DAS REMOTE DUAL BAND. VHF 136-174MHz & UHF 450-512MHz. VHF: +37dBm, UHF: +37dBm, 32filters + 2 Adj sub band per Band, 1 optical port, NFPA, DC, VHF: No Internal Duplexer, UHF: No Internal Duplexer ,UL2524 2nd Edition Listed FIPLEX BY HONEYWELL Fiber DAS

HONBDA-R1D-VUTNNH: Fiber DAS. OTA PUBLIC SAFETY CENTRIC DAS REMOTE DUAL BAND. VHF 136-174MHz & UHF 450-512MHz. VHF: +30dBm, UHF: +37dBm, 32filters + 2 Adj sub band per Band, 1 optical port, NFPA, DC, VHF: No Internal Duplexer, UHF: No Internal Duplexer ,UL2524 2nd Edition Listed FIPLEX BY HONEYWELL Fiber DAS

HONBDA-R2A-VUTNNH: Fiber DAS. OTA PUBLIC SAFETY CENTRIC DAS REMOTE DUAL BAND. VHF 136-174MHz & UHF 450-512MHz. VHF: +30dBm, UHF: +37dBm, 32filters + 2 Adj sub band per Band, 2 optical port, NFPA, AC, VHF: No Internal Duplexer, UHF: No Internal Duplexer ,UL2524 2nd Edition Listed FIPLEX BY HONEYWELL Fiber DAS

HONBDA-R2D-VUTNNH: Fiber DAS. OTA PUBLIC SAFETY CENTRIC DAS REMOTE DUAL BAND. VHF 136-174MHz & UHF 450-512MHz. VHF: +30dBm, UHF: +37dBm, 32filters + 2 Adj sub band per Band, 2 optical port, NFPA, DC, VHF: No Internal Duplexer, UHF: No Internal Duplexer ,UL2524 2nd Edition Listed FIPLEX BY HONEYWELL Fiber DAS

HONBDA-MA-L1NH: Fiber DAS. OTA PUBLIC SAFETY CENTRIC DAS MASTER.UHF 380-400MHz, No Internal Duplexer, +24dBm, 64 filters + 4 Adj sub bands, 8 optical ports, NFPA, class A/B, AC & DC, UL2524 2nd Edition Listed FIPLEX BY HONEYWELL Fiber DAS

HONBDA-MA-L2NH: Fiber DAS. OTA PUBLIC SAFETY CENTRIC DAS MASTER.UHF 406-439MHz, No Internal Duplexer, +24dBm, 64 filters + 4 Adj sub bands, 8 optical ports, NFPA, class A/B, AC & DC, UL2524 2nd Edition Listed FIPLEX BY HONEYWELL Fiber DAS

HONBDA-R1A-L1NH: Fiber DAS. OTA PUBLIC SAFETY CENTRIC DAS REMOTE.UHF 380-400MHz, +37dBm, 64 filters + 4 Adj sub bands, 1 optical port, NFPA, class A/B, AC, No internal Duplexer ,UL2524 2nd Edition Listed FIPLEX BY HONEYWELL Fiber DAS

HONBDA-R1A-L2NH: Fiber DAS. OTA PUBLIC SAFETY CENTRIC DAS REMOTE.UHF 406-439MHz, +37dBm, 64 filters + 4 Adj sub bands, 1 optical port, NFPA, class A/B, AC, No internal Duplexer ,UL2524 2nd Edition Listed FIPLEX BY HONEYWELL Fiber DAS

HONBDA-R1A-UTNH: Fiber DAS. OTA PUBLIC SAFETY CENTRIC DAS REMOTE.UHF 450-512 MHz, +37dBm, 64 filters + 4 Adj sub bands, 1 optical port, NFPA, class A, AC, No internal Duplexer ,UL2524 2nd Edition Listed FIPLEX BY HONEYWELL Fiber DAS

HONBDA-R1A-VNH: Fiber DAS. OTA PUBLIC SAFETY CENTRIC DAS REMOTE.VHF 136-174MHz, +30dBm, 64 filters + 4 Adj sub bands, 1 optical port, NFPA, class A, AC & DC, No Internal Duplexer ,UL2524 2nd Edition Listed FIPLEX BY HONEYWELL Fiber DAS

HONBDA-R1D-L1NH: Fiber DAS. OTA PUBLIC SAFETY CENTRIC DAS REMOTE.UHF 380-400MHz, +37dBm, 64 filters + 4 Adj sub bands, 1 optical port, NFPA, class A/B, DC, No internal Duplexer ,UL2524 2nd Edition Listed FIPLEX BY HONEYWELL Fiber DAS

HONBDA-R1D-L2NH: Fiber DAS. OTA PUBLIC SAFETY CENTRIC DAS REMOTE.UHF 406-439MHz, +37dBm, 64 filters + 4 Adj sub bands, 1 optical port, NFPA, class A/B, DC, No internal Duplexer ,UL2524 2nd Edition Listed FIPLEX BY HONEYWELL Fiber DAS

HONBDA-R1D-UTNH: Fiber DAS. OTA PUBLIC SAFETY CENTRIC DAS REMOTE.UHF 450-512 MHz, +37dBm, 64 filters + 4 Adj sub bands, 1

optical port, NFPA, class A, DC, No internal Duplexer ,UL2524 2nd Edition Listed FIPLEX BY HONEYWELL Fiber DAS

HONBDA-R2A-L1NH: Fiber DAS. OTA PUBLIC SAFETY CENTRIC DAS REMOTE.UHF 380-400MHz, +37dBm, 64 filters + 4 Adj sub bands, 2 optical ports, NFPA, class A/B, AC, No internal Duplexer ,UL2524 2nd Edition Listed FIPLEX BY HONEYWELL Fiber DAS

HONBDA-R2A-L2NH: Fiber DAS. OTA PUBLIC SAFETY CENTRIC DAS REMOTE.UHF 406-439MHz, +37dBm, 64 filters + 4 Adj sub bands, 2 optical ports, NFPA, class A/B, AC, No internal Duplexer ,UL2524 2nd Edition Listed FIPLEX BY HONEYWELL Fiber DAS

HONBDA-R2A-UTNH: Fiber DAS. OTA PUBLIC SAFETY CENTRIC DAS REMOTE.UHF 450-512 MHz, +37dBm, 64 filters + 4 Adj sub bands, 2 optical port, NFPA, class A, AC, No internal Duplexer ,UL2524 2nd Edition Listed FIPLEX BY HONEYWELL Fiber DAS

HONBDA-R2A-VNH: Fiber DAS. OTA PUBLIC SAFETY CENTRIC DAS REMOTE.VHF 136-174MHz, +30dBm, 64 filters + 4 Adj sub bands, 2 optical port, NFPA, class A, AC & DC, No Internal Duplexer ,UL2524 2nd Edition Listed FIPLEX BY HONEYWELL Fiber DAS

HONBDA-R2D-L1NH: Fiber DAS. OTA PUBLIC SAFETY CENTRIC DAS REMOTE.UHF 380-400MHz, +37dBm, 64 filters + 4 Adj sub bands, 2 optical port2, NFPA, class A/B, DC, No internal Duplexer ,UL2524 2nd Edition Listed FIPLEX BY HONEYWELL Fiber DAS

HONBDA-R2D-L2NH: Fiber DAS. OTA PUBLIC SAFETY CENTRIC DAS REMOTE.UHF 406-439MHz, +37dBm, 64 filters + 4 Adj sub bands, 2 optical ports, NFPA, class A/B, DC, No internal Duplexer ,UL2524 2nd Edition Listed FIPLEX BY HONEYWELL Fiber DAS

HONBDA-R2D-UTNH: Fiber DAS. OTA PUBLIC SAFETY CENTRIC DAS REMOTE.UHF 450-512 MHz, +37dBm, 64 filters + 4 Adj sub bands, 2 optical port, NFPA, class A, DC, No internal Duplexer ,UL2524 2nd Edition Listed FIPLEX BY HONEYWELL Fiber DAS

HONBDA-R1A-T0H: Fiber DAS. OTA PUBLIC SAFETY CENTRIC DAS REMOTE.UHF 450-512 MHz, +37dBm, 64 filters + 4 Adj sub bands, 1 optical port, NFPA, class A, AC, Band#1: Narrow Filter internal Duplexer ,UL2524 2nd Edition Listed FIPLEX BY HONEYWELL Fiber DAS

HONBDA-R1A-V3H: Fiber DAS. OTA PUBLIC SAFETY CENTRIC DAS REMOTE.VHF 136-174MHz, +30dBm, 64 filters + 4 Adj sub bands, 1 optical port, NFPA, class A, AC & DC, 3.5MHz BW internal Duplexer ,UL2524 2nd Edition Listed FIPLEX BY HONEYWELL Fiber DAS

HONBDA-R1A-T00H: Fiber DAS. OTA PUBLIC SAFETY CENTRIC DAS REMOTE.UHF DUAL SUB BAND 450-512 MHz, +37dBm, 64 filters + 4 Adj sub bands, 1 optical port, NFPA, class A, AC, Band #1: Narrow Filter, Band #2 Narrow Filter internal Duplexer ,UL2524 2nd Edition Listed FIPLEX BY HONEYWELL Fiber DAS

HONBDA-R1A-TRWCH: Fiber DAS. OTA PUBLIC SAFETY CENTRIC DAS REMOTE.UHF 483.4-484.5/486.4-487.5 & 488.5-489/491.5-492 MHz, +37dBm, 64 filters + 4 Adj sub bands, 1 optical port, NFPA, class A, AC, Internal Duplexer ,UL2524 2nd Edition Listed FIPLEX BY HONEYWELL Fiber DAS

HONBDA-R1A-TWMOH: Fiber DAS. OTA PUBLIC SAFETY CENTRIC DAS REMOTE.UHF 489-491/492-494 & 496.3-497/499.3-500 MHz, +37dBm, 64 filters + 4 Adj sub bands, 1 optical port, NFPA, class A, AC, Internal Duplexer ,UL2524 2nd Edition Listed FIPLEX BY HONEYWELL Fiber DAS

HONBDA-R1A-U04H: Fiber DAS. OTA PUBLIC SAFETY CENTRIC DAS REMOTE.UHF DUAL SUB BAND 450-512 MHz, +37dBm, 64 filters + 4 Adj sub bands, 1 optical port, NFPA, class A, AC, Band #1: Narrow Filter, Band #2 Broadband Filter internal Duplexer ,UL2524 2nd Edition Listed FIPLEX BY HONEYWELL Fiber DAS

HONBDA-R1A-U4H: Fiber DAS. OTA PUBLIC SAFETY CENTRIC DAS REMOTE.UHF DUAL SUB BAND 450-512 MHz, +37dBm, 64 filters + 4 Adj sub bands, 1 optical port, NFPA, class A, AC, Band #1:Broadband Filter internal Duplexer ,UL2524 2nd Edition Listed FIPLEX BY HONEYWELL Fiber DAS

HONBDA-R1D-VTN0H: Fiber DAS. OTA PUBLIC SAFETY CENTRIC DAS
REMOTE DUAL BAND. VHF 136-174MHz & UHF 450-512MHz. VHF:
+30dBm, UHF: +37dBm, 32filters + 2 Adj sub band per Band, 1 optical
port, NFPA, DC, VHF: No Internal Duplexer, UHF: Band#1: Narrow Filter
Internal Duplexer ,UL2524 2nd Edition Listed FIPLEX BY HONEYWELL
Fiber DAS

HONBDA-R1D-VTNRWCH: Fiber DAS. OTA PUBLIC SAFETY CENTRIC DAS REMOTE DUAL BAND. VHF 136-174MHz & UHF 470-512MHz. VHF: +30dBm, UHF: +37dBm, 32filters + 2 Adj sub band per Band, 1 optical port, NFPA, DC, VHF: No Internal Duplexer, UHF: 483.4-484.5/486.4-487.5 & 488.5-489/491.5-4 ,UL2524 2nd Edition Listed FIPLEX BY HON-EYWELL Fiber DAS

HONBDA-R1D-VU304H: Fiber DAS. OTA PUBLIC SAFETY CENTRIC DAS
REMOTE DUAL BAND. VHF 136-174MHz & UHF 450-512MHz. VHF:
+30dBm, UHF: +37dBm, 32filters + 2 Adj sub band per Band, 1 optical
port, NFPA, DC, VHF: 3.5MHz BW Internal Duplexer, UHF: Band#1: Nar-
row Filter Band#2: Broadband Filter Internal Duplexer ,UL2524 2nd Edi-
tion Listed FIPLEX BY HONEYWELL Fiber DAS

HONBDA-R1D-VU34H: Fiber DAS. OTA PUBLIC SAFETY CENTRIC DAS
REMOTE DUAL BAND. VHF 136-174MHz & UHF 450-512MHz. VHF:
+30dBm, UHF: +37dBm, 32filters + 2 Adj sub band per Band, 1 optical
port, NFPA, DC, VHF: 3.5MHz BW Internal Duplexer, UHF: Band#1:
Broadband Internal Duplexer ,UL2524 2nd Edition Listed FIPLEX
BY HONEYWELL Fiber DAS

HONBDA-R1D-VU3MDAH: Fiber DAS. OTA PUBLIC SAFETY CENTRIC DAS REMOTE DUAL BAND. VHF 136-174MHz & UHF 450-470MHz. VHF: +30dBm, UHF: +37dBm, 32filters + 2 Adj sub band per Band, 1 optical port, NFPA, DC, VHF: 3.5MHz BW Internal Duplexer, UHF: 453-454/458-459 & 460-462/465-467MHz ,UL2524 2nd Edition Listed FIPLEX BY HONEYWELL Fiber DAS

HONBDA-R1D-VUN04H: Fiber DAS. OTA PUBLIC SAFETY CENTRIC DAS
REMOTE DUAL BAND. VHF 136-174MHz & UHF 450-512MHz. VHF:
+30dBm, UHF: +37dBm, 32filters + 2 Adj sub band per Band, 1 optical
port, NFPA, DC, VHF: No Internal Duplexer, UHF: Band#1: Narrow Filter
Band#2: Broadband Filter Internal Duplexer ,UL2524 2nd Edition Listed
FIPLEX BY HONEYWELL Fiber DAS

HONBDA-R1D-VUN4H: Fiber DAS. OTA PUBLIC SAFETY CENTRIC DAS
REMOTE DUAL BAND. VHF 136-174MHz & UHF 450-512MHz. VHF:
+30dBm, UHF: +37dBm, 32filters + 2 Adj sub band per Band, 1 optical
port, NFPA, DC, VHF: No Internal Duplexer, UHF: Band#1: Broadband
Filter Internal Duplexer ,UL2524 2nd Edition Listed FIPLEX BY HONEY-
WELL Fiber DAS

HONBDA-R1D-VUNMDAH: Fiber DAS. OTA PUBLIC SAFETY CENTRIC DAS REMOTE DUAL BAND. VHF 136-174MHz & UHF 450-470MHz. VHF: +30dBm, UHF: +37dBm, 32filters + 2 Adj sub band per Band, 1 optical port, NFPA, DC, VHF: No Internal Duplexer, UHF: 453-454/458-459 & 460-462/465-467MHz intern ,UL2524 2nd Edition Listed FIPLEX BY HONEYWELL Fiber DAS

HONBDA-R2D-T0H: Fiber DAS. OTA PUBLIC SAFETY CENTRIC DAS
REMOTE.UHF 450-512 MHz, +37dBm, 64 filters + 4 Adj sub bands, 2
optical port, NFPA, class A, DC, Band#1: Narrow Filter internal Duplexer
UL2524 2nd Edition Listed FIPLEX BY HONEYWELL Fiber DAS

HONBDA-R2D-TRWCH: Fiber DAS. OTA PUBLIC SAFETY CENTRIC DAS
REMOTE.UHF 483.4-484.5/486.4-487.5 & 488.5-489/491.5-492 MHz,
+37dBm, 64 filters + 4 Adj sub bands, 2 optical port, NFPA, class A, DC,
Internal Duplexer ,UL2524 2nd Edition Listed FIPLEX BY HONEYWELL
Fiber DAS

HONBDA-R2D-TWMOH: Fiber DAS. OTA PUBLIC SAFETY CENTRIC DAS
REMOTE.UHF 489-491/492-494 & 496.3-497/499.3-500 MHz, +37dBm,
64 filters + 4 Adj sub bands, 2 optical port, NFPA, class A, DC, Internal
Duplexer .UL2524 2nd Edition Listed FIPLEX BY HONEYWELL Fiber DAS

HONBDA-R2D-U4H: Fiber DAS. OTA PUBLIC SAFETY CENTRIC DAS
REMOTE.UHF 450-512 MHz, +37dBm, 64 filters + 4 Adj sub bands, 2
optical port, NFPA, class A, DC, Band #1: Broadband Filter internal
Duplexer ,UL2524 2nd Edition Listed FIPLEX BY HONEYWELL Fiber DAS

HONBDA-R2D-UMDAH: Fiber DAS. OTA PUBLIC SAFETY CENTRIC DAS
REMOTE.UHF 453-454/458-459 & 460-462/465-467 MHz, +37dBm, 64
filters + 4 Adj sub bands, 2 optical port, NFPA, class A, DC, Internal
Duplexer ,UL2524 2nd Edition Listed FIPLEX BY HONEYWELL Fiber DAS

HONBDA-R2D-UT02H: Fiber DAS. OTA PUBLIC SAFETY CENTRIC DAS
REMOTE DUAL SUB BAND. UHF 450-512 MHz, +37dBm, 32 filters +2 Adj
sub bands, 2 optical port, NFPA, class A, DC, Band#1: Narrow Filter -
Band #2: Narrow Filter, internal Duplexer ,UL2524 2nd Edition Listed
FIPLEX BY HONEYWELL Fiber DAS

HONBDA-R2D-UT22H: Fiber DAS. OTA PUBLIC SAFETY CENTRIC DAS
REMOTE DUAL SUB BAND. UHF 450-512 MHz, +37dBm, 32 filters +2 Adj
sub bands, 2 optical port, NFPA, class A, DC, Band#1: Narrow Filter -
Band #2: Broadband Filter, internal Duplexer ,UL2524 2nd Edition
Listed FIPLEX BY HONEYWELL Fiber DAS

HONBDA-R2D-VT300H: Fiber DAS. OTA PUBLIC SAFETY CENTRIC DAS
REMOTE DUAL BAND. VHF 136-174MHz & UHF 450-512MHz. VHF:
+30dBm, UHF: +37dBm, 32filters + 2 Adj sub band per Band, 2 optical
port, NFPA, DC, VHF: 3.5MHz BW Internal Duplexer, UHF: Band#1: Nar-
row Filter Band#2: Narrow Filter Internal Duplexer ,UL2524 2nd Edition
Listed FIPLEX BY HONEYWELL Fiber DAS

HONBDA-R2D-VT30H: Fiber DAS. OTA PUBLIC SAFETY CENTRIC DAS
REMOTE DUAL BAND. VHF 136-174MHz & UHF 450-512MHz. VHF:
+30dBm, UHF: +37dBm, 32filters + 2 Adj sub band per Band, 2 optical
port, NFPA, DC, VHF: 3.5MHz BW Internal Duplexer, UHF: Band#1: Nar-
row Filter Internal Duplexer ,UL2524 2nd Edition Listed FIPLEX BY HON-
EYWELL Fiber DAS

HONBDA-R2D-VT3RWCH: Fiber DAS. OTA PUBLIC SAFETY CENTRIC DAS REMOTE DUAL BAND. VHF 136-174MHz & UHF 470-512MHz. VHF: +30dBm, UHF: +37dBm, 32filters + 2 Adj sub band per Band, 2 optical port, NFPA, DC, VHF: 3.5MHz BW Internal Duplexer, UHF: 483.4-484.5/486.4-487.5 & 488.5-489/ ,UL2524 2nd Edition Listed FIPLEX BY HONEYWELL Fiber DAS

HONBDA-R2D-VTN00H: Fiber DAS. OTA PUBLIC SAFETY CENTRIC DAS
REMOTE DUAL BAND. VHF 136-174MHz & UHF 450-512MHz. VHF:
+30dBm, UHF: +37dBm, 32filters + 2 Adj sub band per Band, 2 optical
port, NFPA, DC, VHF: No Internal Duplexer, UHF: Band#1: Narrow Filter
Band#2: Narrow Filter Internal Duplexer ,UL2524 2nd Edition Listed
FIPLEX BY HONEYWELL Fiber DAS

HONBDA-R2D-VTN0H: Fiber DAS. OTA PUBLIC SAFETY CENTRIC DAS
REMOTE DUAL BAND. VHF 136-174MHz & UHF 450-512MHz. VHF:
+30dBm, UHF: +37dBm, 32filters + 2 Adj sub band per Band, 2 optical
port, NFPA, DC, VHF: No Internal Duplexer, UHF: Band#1: Narrow Filter
Internal Duplexer ,UL2524 2nd Edition Listed FIPLEX BY HONEYWELL
Fiber DAS

HONBDA-R2D-V1NRWCH: Fiber DAS. OTA PUBLIC SAFETY CENTRIC DAS REMOTE DUAL BAND. VHF 136-174MHz & UHF 470-512MHz. VHF: +30dBm, UHF: +37dBm, 32filters + 2 Adj sub band per Band, 2 optical port, NFPA, DC, VHF: No Internal Duplexer, UHF: 483.4-484.5/486.4-487.5 & 488.5-489/491.5-4 ,UL2524 2nd Edition Listed FIPLEX BY HONEYWELL Fiber DAS

HONBDA-R2D-VU304H: Fiber DAS. OTA PUBLIC SAFETY CENTRIC DAS
REMOTE DUAL BAND. VHF 136-174MHz & UHF 450-512MHz. VHF:
+30dBm, UHF: +37dBm, 32filters + 2 Adj sub band per Band, 2 optical
port, NFPA, DC, VHF: 3.5MHz BW Internal Duplexer, UHF: Band#1: Nar-
row Filter Band#2: Broadband Filter Internal Duplexer ,UL2524 2nd Edi-
tion Listed FIPLEX BY HONEYWELL Fiber DAS

HONBDA-R2D-VU3MDAH: Fiber DAS. OTA PUBLIC SAFETY CENTRIC DAS REMOTE DUAL BAND. VHF 136-174MHz & UHF 450-470MHz. VHF: +30dBm, UHF: +37dBm, 32filters + 2 Adj sub band per Band, 2 optical port, NFPA, DC, VHF: 3.5MHz BW Internal Duplexer, UHF: 453-454/458-459 & 460-462/465-467MHz ,UL2524 2nd Edition Listed FIPLEX BY HONEYWELL Fiber DAS

HONBDA-R2D-VUN04H: Fiber DAS. OTA PUBLIC SAFETY CENTRIC DAS
REMOTE DUAL BAND. VHF 136-174MHz & UHF 450-512MHz. VHF: port,
NFPA, DC. VHF: No Internal Duplexer, UHF: Band#1: Narrow Filter

FLEX 2.0 - High Power Over-the-Air Public Safety Centric Fiber DAS (136-512 MHz)

HONBDA Series

REMOTE.UHF 380-400MHz, +37dBm, 64 filters + 4 Adj sub bands, 1 optical port, NFPA, class A/B, DC, No internal Duplexer ,UL2524 2nd Edition Listed FIPLEX BY HONEYWELL Fiber DAS

HONBDA-R1D-L2NH: Fiber DAS. OTA PUBLIC SAFETY CENTRIC DAS REMOTE.UHF 406-439MHz, +37dBm, 64 filters + 4 Adj sub bands, 1 optical port, NFPA, class A/B, DC, No internal Duplexer ,UL2524 2nd Edition Listed FIPLEX BY HONEYWELL Fiber DAS

HONBDA-R1D-UTNH: Fiber DAS. OTA PUBLIC SAFETY CENTRIC DAS REMOTE.UHF 450-512 MHz, +37dBm, 64 filters + 4 Adj sub bands, 1 optical port, NFPA, class A, DC, No internal Duplexer ,UL2524 2nd Edition Listed FIPLEX BY HONEYWELL Fiber DAS

HONBDA-R2A-L1NH: Fiber DAS. OTA PUBLIC SAFETY CENTRIC DAS REMOTE.UHF 380-400MHz, +37dBm, 64 filters + 4 Adj sub bands, 2 optical ports, NFPA, class A/B, AC, No internal Duplexer ,UL2524 2nd Edition Listed FIPLEX BY HONEYWELL Fiber DAS

HONBDA-R2A-L2NH: Fiber DAS. OTA PUBLIC SAFETY CENTRIC DAS REMOTE.UHF 406-439MHz, +37dBm, 64 filters + 4 Adj sub bands, 2 optical ports, NFPA, class A/B, AC, No internal Duplexer ,UL2524 2nd Edition Listed FIPLEX BY HONEYWELL Fiber DAS

HONBDA-R2A-UTNH: Fiber DAS. OTA PUBLIC SAFETY CENTRIC DAS REMOTE.UHF 450-512 MHz, +37dBm, 64 filters + 4 Adj sub bands, 2 optical port, NFPA, class A, AC, No internal Duplexer ,UL2524 2nd Edition Listed FIPLEX BY HONEYWELL Fiber DAS

HONBDA-R2A-VNH: Fiber DAS. OTA PUBLIC SAFETY CENTRIC DAS REMOTE.VHF 136-174MHz, +30dBm, 64 filters + 4 Adj sub bands, 2 optical port, NFPA, class A, AC & DC, No Internal Duplexer ,UL2524 2nd Edition Listed FIPLEX BY HONEYWELL Fiber DAS

HONBDA-R2D-L1NH: Fiber DAS. OTA PUBLIC SAFETY CENTRIC DAS REMOTE.UHF 380-400MHz, +37dBm, 64 filters + 4 Adj sub bands, 2 optical port2, NFPA, class A/B, DC, No internal Duplexer ,UL2524 2nd Edition Listed FIPLEX BY HONEYWELL Fiber DAS

HONBDA-R2D-L2NH: Fiber DAS. OTA PUBLIC SAFETY CENTRIC DAS REMOTE.UHF 406-439MHz, +37dBm, 64 filters + 4 Adj sub bands, 2 optical ports, NFPA, class A/B, DC, No internal Duplexer ,UL2524 2nd Edition Listed FIPLEX BY HONEYWELL Fiber DAS

HONBDA-R2D-UTNH: Fiber DAS. OTA PUBLIC SAFETY CENTRIC DAS REMOTE.UHF 450-512 MHz, +37dBm, 64 filters + 4 Adj sub bands, 2 optical port, NFPA, class A, DC, No internal Duplexer ,UL2524 2nd Edition Listed FIPLEX BY HONEYWELL Fiber DAS

This document is not intended to be used for installation purposes.
We try to keep our product information up-to-date and accurate.
We cannot cover all specific applications or anticipate all requirements.
All specifications are subject to change without notice.

Fiplex™ is a trademark of Fiplex Communications, Inc.
©2025 by Honeywell International Inc. All rights reserved.
Unauthorized use of this document is strictly prohibited.