

FLEX 2.0 - Public Safety Centric DAS Master (136-869 MHz) (380-400MHz) (406.1-439MHz)

HONBDA-7S-D-RMA
HONBDA-DRMA-Lx

Product Features

- Single stock item, field-programmable for [VHF+UHF] or [700MHz+ FirstNet+800MHz].
- Also available for 380-400MHz and 406.1-439MHz.
- Specifically designed for LMR and Public Safety Applications.
- **FLEX 2.0*** Enhanced Scalability and Flexibility – Remote Unit connection count capability up to 56 using Expansion Units.
- New improved **FLEX 2.0*** user-friendly Graphic User Interface.
- New **FLEX 2.0*** Alarming Features. All alarms of all the Remotes and BBUs of the System are available at the Master Unit.
- Enhanced **FLEX 2.0*** Redundancy Features (optional).
- Inclusion of **FLEX 2.0*** Multiple AGC modes to allow extra Uplink Output Power Per Channel.
- Remote Units equipped with Uplink Squelch and AGC per Channel and Time-Slot (support for P25PH2) to provide truly reduced UL Noise contribution and Near-Far effect mitigation.
- Upon expansion of an existing system, no need to recommission the previously installed sections.
- Isolation Measurement and Isolation Detection in a per Remote Basis. Upon oscillation detection, only the affected area will be turned off.
- Software programmable channel selective or band selective operation, suitable for highly congested RF environments.
- Centralized operation form Master Unit. Single point of access.
- IFC 2015, 2018, 2021 Edition Standard
- NFPA 72 2019 Edition, NFPA 1225 2022 Edition Standard



Applications

- For P25 Ph1, P25 Ph2, DMR, TETRA NXDN and Conventional Systems.
- Tunnels, buildings, subways, airports, stadiums, building campuses, etc.

Specifications

Specifications	Value																				
Fiber-Optic	Single mode Single mode																				
WDM	Yes																				
Optical Wavelengths	1270 / 1330 nm																				
Operational Bands	VHF + UHF, PS700 + Band14 + PS800 (see SKUs at the end of this document) 380 - 400MHz (see SKUs at the end of this document) 406.1 - 439 MHz (see SKUs at the end of this document)																				
Number of Channel Filters	64 channels + 4 Bandwidth Adjustable per band																				
Available Channel Filter BW	For 700/800MHz: 150KHz, 100KHz, 75KHz, 62.5KHz, 50KHz, 37.5KHz, 25KHz, 12.5KHz For UHF/VHF/380-400MHz/406.1-439MHz: 100kHz, 75kHz, 62.5kHz, 50kHz, 37.5kHz, 25kHz, 12.5kHz																				
Group Delay	<table border="1"> <thead> <tr> <th>700/800MHz</th><th>UHF / VHF / 380-400MHz / 406.1-439MHz</th></tr> </thead> <tbody> <tr> <td>Channel Selective 150KHz, 11.5µS</td><td></td></tr> <tr> <td>Channel Selective 100KHz, 13.5µS</td><td>Channel Selective 100kHz, 12.6µS</td></tr> <tr> <td>Channel Selective 75KHz, 16.0µS</td><td>Channel Selective 75kHz, 14.9µS</td></tr> <tr> <td>Channel Selective 62.5KHz, 18.0µS</td><td>Channel Selective 62.5kHz, 16.8µS</td></tr> <tr> <td>Channel Selective 50KHz, 21.0µS</td><td>Channel Selective 50kHz, 19.6µS</td></tr> <tr> <td>Channel Selective 37.5KHz, 25.5µS</td><td>Channel Selective 37.5kHz, 24.1µS</td></tr> <tr> <td>Channel Selective 25KHz, 35.0µS</td><td>Channel Selective 25kHz, 33.4µS</td></tr> <tr> <td>Channel Selective 12.5KHz, 61.5µS</td><td>Channel Selective 12.5kHz, 62.1µS</td></tr> <tr> <td>or Band selective: 3.5 to 6.5µS, depending on BWA</td><td>or Band selective: 3.5 to 6.5µS, depending on BWA</td></tr> </tbody> </table>	700/800MHz	UHF / VHF / 380-400MHz / 406.1-439MHz	Channel Selective 150KHz, 11.5µS		Channel Selective 100KHz, 13.5µS	Channel Selective 100kHz, 12.6µS	Channel Selective 75KHz, 16.0µS	Channel Selective 75kHz, 14.9µS	Channel Selective 62.5KHz, 18.0µS	Channel Selective 62.5kHz, 16.8µS	Channel Selective 50KHz, 21.0µS	Channel Selective 50kHz, 19.6µS	Channel Selective 37.5KHz, 25.5µS	Channel Selective 37.5kHz, 24.1µS	Channel Selective 25KHz, 35.0µS	Channel Selective 25kHz, 33.4µS	Channel Selective 12.5KHz, 61.5µS	Channel Selective 12.5kHz, 62.1µS	or Band selective: 3.5 to 6.5µS, depending on BWA	or Band selective: 3.5 to 6.5µS, depending on BWA
700/800MHz	UHF / VHF / 380-400MHz / 406.1-439MHz																				
Channel Selective 150KHz, 11.5µS																					
Channel Selective 100KHz, 13.5µS	Channel Selective 100kHz, 12.6µS																				
Channel Selective 75KHz, 16.0µS	Channel Selective 75kHz, 14.9µS																				
Channel Selective 62.5KHz, 18.0µS	Channel Selective 62.5kHz, 16.8µS																				
Channel Selective 50KHz, 21.0µS	Channel Selective 50kHz, 19.6µS																				
Channel Selective 37.5KHz, 25.5µS	Channel Selective 37.5kHz, 24.1µS																				
Channel Selective 25KHz, 35.0µS	Channel Selective 25kHz, 33.4µS																				
Channel Selective 12.5KHz, 61.5µS	Channel Selective 12.5kHz, 62.1µS																				
or Band selective: 3.5 to 6.5µS, depending on BWA	or Band selective: 3.5 to 6.5µS, depending on BWA																				
Supported Fiber Loss	20dBo max.																				
Optical Return Loss	>45dB																				
RF Input/Output Impedance	50 Ω																				
Max Operational DL Input Power	-35dBm																				
DL Manual Attenuator	30dB in 1dB steps																				
Maximum UL Output Power	-6 dBm																				
UL IM and Spurious Generation	< -13dBm																				
UL Manual Attenuator	30dB in 1dB steps																				
Overall Gain (Master + Remote)	85dB in DL, 55dB in UL, regardless per length																				
RF Connectors	SMA (f)																				

* A **FLEX 2.0** Master Unit is any PSC DAS Master Unit with firmware version equal or greater than [SW: 5.00].

** A **FLEX 2.0** Remote Unit is any PSC DAS Remote Unit with firmware version equal or greater than [SW: 3.00].

Public Safety Centric DAS Master (136-869 MHz)

HONBDA7S-D-RMA
HONBDA-DRMA-Lx

Specifications

Value

Optical Connectors	LC / UPC
Number of Optical Ports	8 (for Remote Unit and Expansion Unit connection)
Noise Figure	<9dB
Power Supply	110VAC 60Hz & +24 VDC
Power Consumption	40W
Housing	Rack mount, 1 RU.
Environmental	IP30
Temperature Range	-22° to +131° F • -30° to +55° C
Humidity	<95% non-condensing
Dimension and Weight	See table at the end of the document
MTBF	100,000 hours

Control and Alarms

Value

Alarms Report	At Master Unit via USB: Master Unit, Expansion Unit and Remote Unit Status. At Master Unit via Web browser: Master Unit, Expansion Unit and Remote Unit Status. At Master Unit via SNMP: Master Unit, Expansion Unit and Remote Unit Status. At Master Unit, alarms of Master Unit, Expansion Unit and Remote Unit Status can be reported via local Dry Contact or via serial connection to Next Gen BBU. At Remote Unit via USB: Remote Unit Status. At Remote Unit, alarms of Remote Unit can be reported via local Dry Contact or via serial connection to Next Gen BBU.
Master Unit Configuration	Local: USB or Ethernet (Web browser) Remote: Via SNMP or Web browser

Normative

Value

Standards	ITU T G 652 EN60825-1
FCC	FCC, CFR 47, Part 15, Subpart B, Class A Digital devices
FCC ID	P3TDH14-3A / P3TDH14-3A (UHF, VHF)

Model	Type	Dimension	Weight
HONBDA-7S-D-RMA	VHF + UHF / PS700 + FirstNet + PS800, Class A, 8 ports	19 in (482.6mm) rack, 1 RU	20lbs. (9kg)
HONBDA-DRMA-L1	Fiber DAS. DIRECT FEED PUBLIC SAFETY CENTRIC DAS MASTER, Rack mount, UHF 380-400MHz, 24dBm, direct connection, No internal Duplexer, 64ch filters (Class A) + 4 Adb BW (Class B) per band, 8 optical ports, non-over-the-air.	19 in (482.6mm) rack, 1 RU	20lbs. (9kg)
HONBDA-DRMA-L2	Fiber DAS. DIRECT FEED PUBLIC SAFETY CENTRIC DAS MASTER, Rack mount, UHF 406-439MHz, 24dBm, direct connection, No internal Duplexer, 64ch filters (Class A) + 4 Adb BW (Class B) per band, 8 optical ports, non-over-the-air.	19 in (482.6mm) rack, 1 RU	20lbs. (9kg)

Ordering Information

HONBDA-7S-D-RMA: Rack mount, VHF + UHF or 700 + 800 + Band 14, direct connection, 64ch filters (Class A) + 4 Adb BW (Class B) per band, 8 optical ports, non-over-the-air.

HONBDA-DRMA-L1: Fiber DAS. DIRECT FEED PUBLIC SAFETY CENTRIC DAS MASTER, Rack mount, UHF 380-400MHz, 24dBm, direct connection, No internal Duplexer, 64ch filters (Class A) + 4 Adb BW (Class B) per band, 8 optical ports, non-over-the-air.

HONBDA-DRMA-L2: Fiber DAS. DIRECT FEED PUBLIC SAFETY CENTRIC DAS MASTER, Rack mount, UHF 406-439MHz, 24dBm, direct connection, No internal Duplexer, 64ch filters (Class A) + 4 Adb BW (Class B) per band, 8 optical ports, non-over-the-air.

Standards and Codes

These listings and approvals apply to the modules specified in this document. In some cases, certain modules or applications may not be listed by certain approval agencies, or listing may be in process. Consult the factory for latest listing status.

- FCC (Federal Communications Commission) Complaint
- IC Compliant
- IFC 2015, 2018, 2021 Edition Standard
- ISO 9001 PECB Certified
- NFPA 72 2019 Edition, NFPA 1225 2022 Edition Standard
- RoHS Compliant

This document is not intended to be used for installation purposes.
We try to keep our product information up-to-date and accurate.
We cannot cover all specific applications or anticipate all requirements.
All specifications are subject to change without notice.

Fiplex™ is a trademark of Fiplex Communications, Inc.
©2022 by Honeywell International Inc. All rights reserved.
Unauthorized use of this document is strictly prohibited.